

Searching PAJ

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-181380
(43)Date of publication of application : 06.07.1999

(51)Int Cl

C09J109/02
C09J 11/04
C09J163/00
H05K 3/38

(21)Application number : 09-350780
(22)Date of filing : 19.12.1997

(71)Applicant : MITSUI CHEM INC
(72)Inventor : ISHIGURO MASAHARU

(54) FLAME-RETARDANT ADHESIVE COMPOSITION

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a flame-retardant adhesive compsn. which is excellent in adhesiveness, resistances to soldering heat and heat aging, and flame retardance and is useful as an adhesive for flexible printed circuit substrates.
SOLUTION: This compsn. contains (A) 1 pt. carboxylated nitrile-butadiene rubber, (B) 0.01-0.25 pt. poly-N-glycidyl epoxy resin, (C) 1.0-4.0 pts. at least difunctional epoxy resin having no N-glycidyl group, (D) 0.3-1.1 pts. resin-coated red phosphorus flame retardant having an average particle size of 5 μ m or lower, and (E) 0.4-2.0 pts. auxiliary flame retardant comprising a silane-treated metal hydroxide of the group 2 or 3.

LEGAL STATUS

[Date of request for examination]
[Date of sending the examiner's decision of rejection]
[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]
[Date of final disposal for application]
[Patent number]
[Date of registration]
[Number of appeal against examiner's decision of rejection]
[Date of requesting appeal against examiner's decision of rejection]
[Date of extinction of right]

Copyright (C): 1998,2000 Japan Patent Office